

5 cm

| BORE N° | DEPTH TO BEDROCK | TIN CONTENT<br>OZ. PER CU. YD. OF 70% |
|---------|------------------|---------------------------------------|
| 1 1931  | 170 FEET         | 0.45                                  |
| 2       | 149              | 0.52                                  |
| 3       | 180              | 0.76                                  |
| 4       | 190              | 0.47                                  |
| 5       | 198              | 0.44                                  |
| 6       | 203              | 0.20                                  |
| 7       | 173              | 0.51                                  |
| 8       | 174              | 0.34                                  |
| 1 1937  | 148              | 1.25                                  |
| 2       | 142              | 2.91                                  |
| 3       | 99               | 2.01                                  |
| 4       | 144              | 2.22                                  |
| 5       | 102              | 1.29                                  |
| 6       | 54               | 0.64                                  |
| 7       | 54               | 1.33                                  |
| 8       | 138              | 2.89                                  |
| 9       | 146              | 1.64                                  |

Holes 20-21 Failing 1500' Not  
200 Percussion Bathymetry  
A130-133 Gamma Ray



## - LEGEND -

- TERTIARY  
Basalt.
- Sand, clay & pebbly gravel - poorly exposed.
- DEVONIAN  
Granitic rocks.
- SILURIAN  
Mafic group - metasediments.
- Workings.
- I.P. Traverses lines.
- River flats.
- Resistivity.

CONTOURED RESISTIVITY

SECOND SEPARATION

UTAH DEVELOPMENT COMPANY

I.P. TRAVERSES

ARBA AREA, TASMANIA

SCALE: 1" = 400'

DATE: MARCH 15, 1965

GEOLOGY BY: O.N.W. &amp; W.R.A.

