

AIRBORNE SURVEY EQUIPMENT

Aircraft	AS-350BA "Squirrel" helicopter VH-RTV
Electromagnetic System	Hummingbird towed 30m below aircraft, multi-coil, five frequency system manufactured by Geotech Pty Ltd of Toronto, Canada
Operating Frequencies	Coplanar coils at 880, 6608 and 34133 Hertz plus coaxial coils at 980 and 7001 Hertz
Magnetometer	Geometrics G-822A Caesium Vapour Resolution 0.001 nT
Recording Interval	Electromagnetic system 0.1 sec (approx 3.5 metres) Magnetometer 0.1 sec (approx 3.5 metres)
EM System Clearance	EM & magnetic sensor boom 30 metres
Navigation	Real time differential GPS system Ashtech G12 receiver Omnistar LR3000 virtual base station
Acquisition System	Geo Instruments Model 2002


FLIGHT PATH PROCESSING

Flight path calculated from differentially corrected GPS Data using a Fugro Omnistar 3000LR differential corrector incorporating an Ashtech G12 GPS engine.
GPS navigation data differentially corrected in real time.



AIRBORNE SURVEY SPECIFICATIONS

Flight Line Direction	000 - 180 degrees
Flight Line Separation	200 metres
Tie Line Direction	090 - 270 degrees
Tie Line Separation	2000 metres
Terrain Clearance	60 metres
Survey flown	November 2001
Geo Instruments job number	2113



DATUM : AGD66
PROJECTION : AMG
ZONE : 55

WESTERN TASMANIAN REGIONAL MINERALS PROGRAM
DOLCOATH GRANITE

Airborne Geophysical Survey
Flight Path

DATE: July 2002	BY: Geo Instruments	PLAN NO.
SCALE: 1:50 000	REF.	