

UR 1957/128A

128A

KLE/L

4th July, 1957

MEMORANDUM

VISIT TO G33 PERCUSSION DRILL TRIABUNNA
DISTRICT, WEDNESDAY, 3RD JULY, 1957.

Left Hobart at 8.30 a.m. and arrived Triabunna
10.30 a.m.

Delivered

- 1 New 2" square faced Flatter
- 1 3 ft. $\frac{3}{8}$ " bolt nuts and $\frac{1}{8}$ " plate washers
- 1 $\frac{3}{8}$ " x $\frac{3}{8}$ ") double ended Whitworth ring spanners
- 1 $\frac{3}{8}$ " x 1") NEW
- 1 drum of approximately 250' good drill cable left
in my yard by L. Fletcher.

Drill advanced to 54 feet through sand, (cased)
and in grey sticky shale with pieces of coarse dolomite
gravel.

Driller using under cutting bit - making slow
progress, about 10 ft. per shift. Claims the slotted
drive pump he requested would be ideal for greater progress
in this type of ground because easy to clean out. Also
the open ended clay tool described and sketched with
previous memo.

Requirements

- 2 Bolts for drive clamps, 14" long 1 $\frac{1}{4}$ " diameter
6 ins. of VEE thread approx. 5 thread to 1"
(Could be made or supplied by P.W.D.)

Order from Goldfields (air freight):

For Jack shaft assembly

- 2 Cod pieces - G33/1/10
- 1 Masonite laminated G33/1/2 Friction wheel
- 1 eccentric and bush for Sandreel Assembly G33/10/5.

Note: The sand reel sticks at times when pulling out of
drill hole.

Left Triabunna at 5 p.m. and arrived Hobart 6.45p.m.

KLE

(K.L. Evans)

DRILLING SUPERINTENDENT

The Director of Mines,
HOBART.