AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

APPENDIX I

Area: STH. MT. CAMERON BONSER CREEK Hole No: B.C.2 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Percussion

Surface R.L.: 54.3 m Basement R.L.: 44.7 m Cutting Shoe / Bit diameter: 16.02cm. Theoretical Volume: 40.3 litres

Date: 9/9/81 Driller: G. Selby Assistant: B. Blake Sample Washer: S. Moore Geologist: R. Munro

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	5459	19LTRS	84.9	0.17	0.21	10.9	6.3	Black mud, c & f sand, heavy drift, hard granite pebbles. V. f. tr. of tin, ilmenite, monazite.
2	4	5460	28½ "	118.5	0.07	0.12	4.1	3.6	C & f sand, heavy drift, hard granite pebbles. Tr. of tin, ilmenite, pyrite.
4	6	5461	21 "	137.9	0.07	0.14	6.6	4.2	C & f sand, heavy drift, hard granite pebbles. Pyrite, ilmenite.
6	8	5462	23 "	123.7	0.05	0.09	3.8	2.7	C & f sand, black mud, heavy drift, hard granite pebbles. Pyrite.
8	10	5463	24½"	110.5	0.77	1.22	49.6	37.7	C & f sand, heavy drift, hard granite rock. Sm. amount c. tin, pyrite.
									648014

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 9.60 m. Grade from surface to inferred basement at ..... m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement ..... l. at 96 m 11 g SnO_2/m^3 +