AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: STH.MT. CAMERON-BONSER CREEK Hole No: B.C.5 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Percussion

Surface R.L: 51.3 m Basement R.L: 42.8 m Cutting Shoe / Bit diameter: 16.02 Theoretical Volume: 40.3 litres

Date: 10/9/81 Driller: G. Selby Assistant: B. Blake Sample Washer: S. Moore Geologist: R. Munro

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	5478	27LTRS	133.1	0.11	0.21	7.7	6.5	Black mud, c & f sand, heavy drift. Ilmenite, pyrite.
2	4	5479	24 "	157.9	0.02	0.05	1.8	1.4	Mud, c & f sand, heavy drift. Ilmenite, pyrite.
4	6	5480	16 "	126.1	0.06	0.11	6.7	3.3	C & f sand, black mud. Ilmenite, pyrite.
6	8	5481	30 "	124.4	12.04	21.40	713.3	663.6	C & f sand, med & lge. wash, heavy drift. Tin, ilmenite.
8	9	5482	17 "	133.9	5.44	10.40	612.1	645.5	C & f sand, decomposed granite. Sm. amount tin, pyrite.
9	10	5483	16½"	159.3	1.34	3.05	184.8	189.2	Decomposed granite. Pyrite.
10	11	5484	12½"	128.9	0.08	0.15	11.8	9.1	Decomposed granite.

648017

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 8.50 m. Grade from surface to inferred basement at ..... m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement ..... l at 8.5 m 258 g SnO_2/m^3 +