

AUSTRALIAN ANGLO AMERICAN LIMITED

016

PROSPECT: EL 22/80

AREA: SOUTH ESK

STATE: TASMANIA

Bore no: B1-A

Commenced time: 3.45 PM

Date: 18.3.81

Machine: GEMCO 210B

Casing shoe diameter: External 9.0cm
Internal 7.5cm

SHEET 1/2

Off-set: -

Completed time: 6.00 PM

Date: 19.3.81

Foreman partner: A. JACKSON

Supervisor: S. DOUGLAS

Collar level: _____

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000 lts. cu.m)		ACTUAL VOLUME			WT. OF MATERIALS (kg)	WT (%)			FIELD CONCENTRATE					REMARKS	
				section	cum.	section (1000 lts. cu.m)	cum. (1000 lts. cu.m)	section vol. rec. (%)		SANDS / GRAVELS			CLAY	actual wt. (g) record.	Au (mg) per gram Au (ppm)	metre-gram	cum. metre-gram		prop. wt. (g) per cu. m.
										+10 mm	-10 mm + 20 #	-20 #							
0-1	1	Ochre sands & gravels	F			7.0	7.0		13.3					12.50	-				Cased only
1-2	1	" " "	F			7.0	14.0		17.3					10.95	-				Dilled then cased.
2-3	1	Ochre clays	M			6.0	20.0		9.3					9.37	-				" " "
3-4	1	Ochre sandy clays	M			7.0	27.0		11.2					11.24	-				
4-5		" " "	M			7.0	34.0		12.9					14.46	-				
5-6		" " "	M			8.0	42.0		15.7					14.50	-				
6-7		" " "	M			9.0	51.0		17.7					11.12	-				
7-8		" " "	M			7.0	58.0		10.2					16.09	-				
8-9		" " "	M			6.0	64.0		9.4					14.00	-				
9-10		" " "	M			6.0	70.0		10.9					7.50	-				

Bottomed / ~~unbottomed~~ at 13 metres on Maitimo bedrock
Shales

Average field grade _____ g. per cu. m.

AUSTRALIAN ANGLO AMERICAN LIMITED

017

PROSPECT: EL 22/80

AREA: SOUTH ESK

STATE: TASMANIA

Bore no: B1-A

Commenced time: _____

Date: _____

Machine: _____

Casing shoe diameter: _____

SHEET 212

Off-set: _____

Completed time: _____

Date: _____

Foreman
ponner: _____

Supervisor: _____

Collar level: _____

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000ths cu.m.)		ACTUAL VOLUME			WT OF MATERIALS (Kg)	WT (%)			FIELD CONCENTRATE					REMARKS	
				section	cum.	section (1000ths cu.m.)	cum. (1000ths cu.m.)	section vol. rec (%)		SANDS / GRAVELS			CLAY	actual wt (g) record.	D ₅₀ (mm) (g)	metre-gram	cum. metre-gram		prop. wt. (g) per cu. m.
										+10 mm	-10 m + 20 #	-20 #							
10-11		Ochre sandy clays	M			7.0	77.0		13.0					11.15	-				
11-12		" " "				10.0	87.0		17.7					11.75	-				
12-13		" " "				5.0	92.0		9.9					13.65	-				
13-14		Weathered, grey laminated shales																	CORED. Recovered 1.0m.
		EDH SILTS				4.0	96.0		6.7					11.66	-				