

058

## AUSTRALIAN ANGLO AMERICAN LIMITED

PROSPECT: EL 22/80AREA: SOUTH EBKSTATE: TASMANIABore no.: C6Commenced time: 9:30 AMDate: 18.3.81Machine: GENCO 2103Casing shoe diameter: External 9.0 cm  
Internal 7.5 cmOff-set: —Completed time: 2:15 PMDate: 18.3.81Foreman  
partner: A. JACKSONSupervisor: S. DOUGLASCollar level: —

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL (1000ths cu.m.)		ACTUAL VOLUME			WT OF MATERIALS (Kg)	WT (%)			FIELD CONCENTRATE					REMARKS	
				section	cum.	section (1000ths cu.m.)	cum. (1000ths cu.m.)	section vol. rec. (%)		SANDS/GRAVELS			CLAY	actual wt. (g) record	Au (ppm) per Au (ppm) cum.	metre-gram	cum. metre-gram		prog. wt. (g) per cu. m.
										+10 mm.	-10 m + 20 #	-20 #							
0-1	1	Brown sand & silt	F			6.0	6.0		6.3					9.05	—				Cased only.
1-2	1	" " "	F			7.0	13.0		9.8					15.00	—				Dolled then cased.
2-3	1	Coarse gravels of dolerite & sandstone	F			0.5	13.5		2.4					10.97	0.002 0.205				
3-4	1	Sandy gravels	F			4.0	17.5		5.7					18.83	—				
4-5	1	" "	F			5.0	22.5		8.8					8.28	—				
5-6	1	" "	F			10.0	32.5		17.6					10.30	0.001 0.097				
6-7	1	Grey sandy clays	M			5.0	37.0		9.1					10.68	—				
7-8	1	Grey clay	S			2.0	39.0		3.5					23.27	—				
8-9	1	Weathered grey shales																	Cored. Recovered 1.0m.
		EBK silts				5.0	44.0		8.2					9.39	—				

Bottomed / ~~at~~ at 8.0 metres on Mahinna bedrock  
shales

Average field grade \_\_\_\_\_ g. per cu. m.

940113