

AUSTRALIAN ANGLO AMERICAN LIMITED

060

PROSPECT: EL 22/20

AREA: SOUTH ESK

STATE: TASMANIA

Bore no.: C 7

Commenced time: 2:00PM

Date: 17. 3. 81

Machine: GMCO 310 B

Casing shoe diameter: External 9.0cm
Internal 7.5cm

SHEET 1/1

Off-set: -

Completed time: 9:00AM

Date: 18. 3. 81

Foreman: A. JACKSON

Supervisor: S. DOUGLAS

Collar level: _____

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000ths cu.m)		ACTUAL VOLUME			WT. OF MATERIALS (%)	WT. (%)			FIELD CONCENTRATE					REMARKS	
				section	cum.	section	cum.	section vol. rec. (%)		SANDS/GRAVELS			CLAY	actual wt. (g) recovd.	Au (mg) per Au (ppm) calcn.	metre-gram	cum. metre-gram		prog. wt. (g) per cu. m.
										+10 mm	-10 m + 20 #	-20 #							
0-1	1	Brown sands & silt	F			3.0	3.0		4.3					11.47	0.009 0.784				Cased only
1-2	1	Ochre-brown gravelly sands	F			4.0	7.0		7.7					10.24	-				Drilled then cased
2-3	1	" " " "	F			14.0	21.0		25.3					19.41	0.001 0.028				" " "
3-4	1	Grey sands with quartz chips	F			5.0	26.0		10.3					8.32	-				" " "
4-5	1	Grey clay	S			3.0	29.0		5.7					15.23	-				" " "
5-6	1	" " "	S			5.0	34.0		10.8					8.23	-				" " "
6-7	1	Weathered grey laminated shales with quartz veins & pyrite																	Cored. Recovered 0.6m.
		EOH Silts				3.0	37.0		9.5					3.91	-				

Bottomed / ~~terminated~~ at 4.0 metres on Mafic bedrock shale

Average field grade _____ g. per cu. m.

949115