

AUSTRALIAN ANGLO AMERICAN LIMITED

173

PROSPECT: EL22/80

AREA SOUTHEAST

STATE: TASMANIA

Bore no: H 1

Commenced time: 12:00PM

Date: 15.5.81

Machine: GEMCO210B

Casing shoe diameter: External 9.3 cm
Internal 7.5 cm.

Off-set: _____

Completed time: 10:00AM

Date: 21.5.81

Foreman/panner: A. JACKSON

Supervisor: S. DOUGLAS

SHEET 1/2

Collar level: _____

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000ths. cu.m)		ACTUAL VOLUME			WT OF MATERIALS (Kg)	WT (%)			FIELD CONCENTRATE					REMARKS		
				section	cum.	section (1000ths. cu.m)	cum. (1000ths. cu.m)	section vol. rec. (%)		SANDS/GRAVELS			CLAY	actual wt. (g) record.	Au (mg) per Pu (ppm) count	metre-gram	cum. metre-gram		prog. wt. (g) per cu. m.	
										+10 mm	-10 m + 20 #	-20 #								
0-1	1	Ochre clayey sands	F			7.0	7.0		14.4					15.06	0.380 25.1					cased only. 1 colour.
1-2	1	Coarse sands & gravel	F			8.0	15.0		15.3					4.92	0.685 129					Drilled then cased 4 colours
2-3	1	Brown-ochre sandy clay	M			8.0	23.0		15.4					11.01	0.001 0.110					
3-4	1	Brown clayey sand	M			11.0	34.0		17.1					14.90	TR 0.037					Probably weathered dolerite
4-5	1	" " "	M			5.0	39.0		12.9					13.32	TR 0.015					
5-6	1	" " "	M			4.0	43.0		9.7					2.43	-					
6-7	1	" " "	M			10.0	53.0		19.5					6.16	-					
7-8	1	" " "	M			8.0	61.0		14.8					15.13	-					
8-9	1	" " "	M			7.0	68.0		14.7					15.52	-					
9-10	1	Grdy rock chips & clay	M			7.0	75.0		14.0					3.06	-					

Bottomed/Unbottomed at 10.0 metres on Dolerite bedrock.

Average field grade _____ g. per cu. m.

949228

