

188

AUSTRALIAN ANGLO AMERICAN LIMITED

PROSPECT: EL22/80

AREA: SOUTH ESK

STATE: TASMANIA

Bore no.: I 6

Commenced time: 10.00 AM

Date: 26.5.81

Machine: GEMCO 2108

Casing shoe diameter: External 9.3cm
Internal 7.5cm

Off-set: -

Completed time: 11.00 AM

Date: 27.5.81

Foreman/panner: A. JACKSON

Supervisor: S. DOUGLAS

SHEET 1/1

Collar level: _____

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000 lbs. cu. m.)		ACTUAL VOLUME			WT OF MATERIALS (Kg)	WT (%)			FIELD CONCENTRATE					REMARKS		
				section	cum.	section (1000 lbs. cu. m.)	cum. (1000 lbs. cu. m.)	section vol. rec. (%)		SANDS/GRAVELS			CLAY	actual wt. (g) record	AU (mg per g) (mg per g)	metre-gram	cum. metre-gram		prog. wt. (g) per cu. m.	
										+10 mm	-10 m +20 #	-20 #								
0-1	1	Ochre clays	M			11.0	11.0		19.4					1.97	-					Cased only
1-2	1	" "	M			13.0	24.0		20.2					13.06	0.006 0.492					Drilled, then cased
2-3	1	Ochre sandy clay	M			9.5	33.5		17.1					1.30	-					Probably weathered sandstone
3-4	1	" " "	M			10.0	43.5		13.7					14.04	TR 0.015					
4-5	1	" " "	M			10.0	53.5		19.6					8.88	FR 0.065					
5-6	1	" " "	M			15.0	68.5		24.0					13.69	-					
6-7	1	" " "	M			8.0	76.5		14.1					11.37	-					
7-8	1	" " "	M			9.0	85.5		16.2					13.07	-					
8-9	1	" " "	M			5.0	90.5		11.5					3.99	-					
9-10	1	Ochre sandstone with quartz veins																		Cased. Recovered 1.0m.
		EDH SILTS				8.0	98.5		16.5					3.45	-					

Bottomed / Unbottomed at 9.0 metres on Mafic bedrock Sandstone

Average field grade _____ g. per cu. m.

949243