

AUSTRALIAN ANGLO AMERICAN LIMITED

190

PROSPECT: EL 22/80

AREA: SOUTH ESK

STATE: TASMANIA

Bore no.: J5

Commenced time: 2:30 PM

Date: 28.5.81

Machine: GEMCO 210 B

Casing shoe diameter: External 9.3 cm  
Internal 7.5 cm

Off-set: 25m →

Completed time: 11:00 AM

Date: 29.5.81

Foreman/panner: A. JACKSON

Supervisor: S. DOUGLAS

SHEET 1/1

Collar level: \_\_\_\_\_

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000ths cu m)		ACTUAL VOLUME			WT OF MATERIALS (kg)	WT (%)			FIELD CONCENTRATE					REMARKS	
				section	cum.	section (1000ths cu m)	cum. (1000ths cu m)	section vol. rec. (%)		SANDS/GRAVELS			actual wt (g) recovd	Au (mg per Au (ppm))	metre-gram	cum. metre-gram	prog. wt. (g) per cu. m.		
										+10 mm	-10 m + 20 #	-20 #							CLAY
0-1	1	Brown sand; ochre sandy clays	M			6.0	6.0		14.0					11.36	-				Cased only.
1-2	1	Ochre sandy clays	S			10.0	16.0		18.1					5.53	-				Dilled then cased
2-3	1	" " "	S			7.0	23.0		16.2					8.88	-				
3-4	1	Ochre sandy clays; dolerite chips	M			5.0	28.0		11.1					4.99	-				
4-5	0.5	Dolerite & clays																	CORED 0.4m. Recovered 0.3. Difficult to core
		EOH silts				6.0	34.0		13.8					12.37	-				

Bottomed/Unbottomed at 4.0 metres on dolerite bedrock

Average field grade \_\_\_\_\_ g. per cu. m.

949245