

AUSTRALIAN ANGLO AMERICAN LIMITED

192

PROSPECT: EL 22/80

AREA: SOUTH ESK

STATE: TASMANIA

Bore no: J6

Commenced time: 11:30 AM

Date: 29.5.81

Machine: GENCO 2103

Casing shoe diameter: External 9.3  
Internal 7.5

Off-set: -

Completed time: 2:45 PM

Date: 29.5.81

Foreman/panner: A. JACKSON

Supervisor: S. DOUGLAS

Collar level: \_\_\_\_\_

DEPTH (m)	THICKNESS (m)	DESCRIPTION OF GROUND	TENACITY	THEORETICAL VOL. (1000ths cu.m.)		ACTUAL VOLUME			WT OF MATERIALS (Kg)	WT (%)			FIELD CONCENTRATE					REMARKS	
				section	cum	section (1000ths cu.m.)	cum (1000ths cu.m.)	section vol. rec (%)		SANDS/GRAVELS			CLAY	actual wt (g) recovd	Au (ppm) (sum Au ppm)	metre-gram	cum. metre-gram		prog. wt. (g) per cu. m.
										+10 mm	-10 mm + 20 #	-20 #							
0-1	1	Brown sands; ochre clays	S			3.0	3.0		6.0					4.13	-				Cased only
1-2	1	brown-ochre clays	S			5.0	8.0		8.6					12.94	-				Drilled then cased.
2-3	1	brown-ochre clays; rock chips	S			4.0	12.0		9.2					9.44	-				
3-4	1	Brown sands & rock chips	M			7.0	19.0		13.0					9.44	-				
4-5	1	" " " "	M			8.0	27.0		14.8					4.95	-				
5-5.70.7	0.7	Dolerite																	CORED
		EOT silts				3.0	30.0		6.3					17.55	-				

Bottomed / Unbottomed at 5.0 metres on dolerite bedrock

Average field grade \_\_\_\_\_ g. per cu. m.

940247