AAR LIMITED

CSR

952022

HOLE No. 2

PAGE 1 OF 2

PROJECT AREA: LAUNCESTON — PROJECT No. 32852

SPUDDED: 16-3-81 — COMPLETED: 17-3-81

LOCATION: 2Km South of Longford — CO-ORDS: X: 5098 E. 53914 N

ELEVATION: 150m asl — DIRECTION: — INCLINATION: -90° — TOTAL DEPTH: 91m

HOLE TYPE: O/H - core - O/H. (125mm, 85mm) — DRILLING CONTRACTOR: Exp. Perc. WA — DRILLER: A Fanso

LOGGED BY: BH + RO — DATE: 17.3.81 — BIT SIZE: O/H TO 68m — Hall TO 71m — O/H TO 91m.

CORE RECOVERY	METRAGE	DESCRIPTION	Core bedd'g angle and joint spacing	LOG SCALE: 1:	SAMPLE No.	Assayed length	ASSAY VALUE
		0-5m CLAY: mottled red. brown-blue grey SILTY CLAYS WITH OCCASIONAL QUARTZ pebbles					
		5-7m CLAY: MOTTLED red brown + blue grey SLIGHTLY SILTY WITH Red OCHRE SILTY INCLUSIONS, CLAYS PLASTIC + SOFT		CASING TO 7m			
	10	7-11m CLAY: interbedded blue-grey PLASTIC CLAY WITH SILTY NON PLASTIC brown CLAY, SOFT.					
		11-47m. THINLY bedded BLUE GREY PLASTIC CLAY WITH BROWN SILTY CLAY - SLIGHTLY INDURATED WITH WEAK FISSILITY + CONCHOIDAL FRACTURE ALTERNATING SANDS.					
	20						
		(28-30m) INTERBEDS OF DARK BROWN					
	30	CLAY WITH RARE SOFT BLACK WOODY PARTICLES					
	40						

952023

HOLE No 2

CORE RECOVERY	METRAGE	DESCRIPTION	Core bedd'g angle and joint spacing	LOG SCALE: 1:	SAMPLE No.	Assayed length	ASSAY VALUE SGS GLO463 Oil yield (L/t) (Zero Moist)	Water Yield (L/t)	Gas Sp. Gr.	Gas + Loss (kg/t)	Residue (kg/t)	Moisture %
		42-57m GRAVELS + pebbles LOOSE WELL ROUNDED MAINLY QUARTZ, QUARTZITE - SILTSTONE APPEAR UNCONSOLIDATED										
	50											
		(57-68m) HOLE HIGHLY CONTAMINATED SUSPECT DARK BROWN SOFT CLAY WITH WOOD FRAGMENTS ALTERNATING WITH THIN <1m LIGNITE BANDS										
	60											
68m												
1.2m	70	CORE IMMEDIATELY SHEATHED 30cm OF SOFT DARK BROWN PLASTIC CLAY WITH WOOD FRAGMENTS AND 30cm OF BLACK LIGNITE. FRIABLE, CONTAINING SILT + CLAY (CLASTS) TO 2cm.		68-71	L0201 LIGNITE	0.9 m.	35	224	0.962	69	679	16.7
71m					L0202 CLAY	0.3 m.	<1	84	—	3	913	5.6
		(71-91) AS PER ABOVE ALTERNATING BANDS OF DARK BROWN SILTY CLAYS + THIN LIGNITE BANDS										
	80											
		(CASED HOLE TO 50m WITH 100mm CASING FOR WATER BORE)										
		(RADIOMETRIC RESPONSE - SCINTREX SCINTILLOMETER 50-55 CPS RANGE OVER ENTIRE HOLE)										
	90											