99-1030

AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area STH. MT. CAMERON Hole No B.P.44 Collar Co-ordinates ..... mN ..... mE Drilling Method **Percussion**

Surface R.L. 73.0 m Basement R.L. 57.5 m Cutting Shoe / Bit diameter **16.03 cm..** Theoretical Volume 40.3 litres

Date 5/3/81 Driller **G. Selby** Assistant **B. Blake** Sample Washer **S. Moore** Geologist **R. Munro**

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	5413	3LTRS	202.0	0.10	0.29		4.5	C & f sand, (tailings). Pyrite.
2	4	5414	17½"	12				4.5	Black mud, c & f sand. Pyrite.
4	6	5415	18 "	126.7	7.67	13.88		430.6	Black mud, c & f sand, med. quartz wash. Tin, ilmenite, pyrite.
6	8	5416	20 "	123.2	7.32	12.88		399.6	C & f sand, white clay, heavy drift. Tin, ilmenite, pyrite.
8	10	5417	28 "	135.3	2.73	5.28		163.7	C & f sand, heavy drift, white clay. Sm. amount tin, ilmenite, pyrite.
10	12	5418	15 "	173.1	0.14	0.35		10.7	C & f sand, heavy drift, white clay. V. f. tr. of tin, pyrite.
12	14	5419	17½"	231.9	0.04	0.13		4.1	C & f sand, heavy drift, brown clay. Pyrite.
14	16	5420	19½"	148.2	0.03	0.06		2.0	C & f sand, brown clay, decomposed granite. Pyrite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Record factored theoretical volume to recovered tin

Drillers reported basement at 15.50 m Grade from surface to inferred basement at ..... m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 133.6 at 15.5 m 132 g SnO_2/m^3 +

Total recovered tin 32.87 g SnO_2

Dwg no ...