

24

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: GLADSTONE Drill: G.33. PERCUSSION.
 Bore No.: 4. (A. LINE 5300) Commenced: 4. 27. 5. 58 5. 4. 6. 58 Completed: 4. 30. 5. 58 5. 9. 6. 58
 Location of Bore: BETWEEN LITTLE AND BIG BOOBYALLA RIVERS. Ref No: 1262 1263
 Co-ordinates of Collar: General AMG Co-ords: 584800E 5465000N R.L. of Collar: _____
 Bearing: Bore not Placed. Inclination: _____ Final Depth: 86 feet (hole 4) 108 feet (hole 5)

392

BORE LOG

Date	Footage	Total Depth	From	To	Core	Thickness	Particulars of Core	Details of Ore Intersection
1958								
May 27	33'	33'	0'	3'	-	3'	Soil and gravel.	
" 28	19	52'	3'	5'	-	2'	CEMENTED DRIFT.	
" 29	28	80'	5'	21'	-	16'	Drift.	
" 30	6	86'	21'	28'	-	7'	Wash.	
			28'	33'	-	5'	Pug.	
			33'	42'	-	9'	Cemented Shingle Wash.	
			42'	82'	-	40'	Marine Mud with wash. Some boulders.	
			82'	86'	-	4'	Granite	
BORE NO. 5. SCOTIA LEAD								
JUNE 4	30'	30'	0'	2'	-	2'	Sandy Soil.	
" 5	35'	65'	2'	15'	-	13'	Puggy drift with angular wash	
" 6	20'	85'	15'	30'	-	15'	Brown silt with seams of lignite	
" 9	85'	108'	30'	32'	-	2'	Sand.	
			32'	40'	-	8'	Puggy drift.	
			40'	65'	-	25'	Coarse gravel and brown silt.	
			65'	85'	-	20'	Pug to a sandstone with lignite seams.	
			85'	96'	-	11'	Cemented granite drift with lignite seams.	
			96'	108'	-	12'	Slate.	

11 291