AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.4 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 50.02 m Basement R.L.: 45.02 m Cutting Shoe / Bit diameter: 80mm Theoretical Volume: 10.1 litres

Date: 31/1/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9052	8	130.4	0.27	0.50	62.9	62.3	Fine silty sand, yellow clay. Very fine trace of tin, ilminite,& monozite.
2	4	9053	4	135.1	0.20	0.39	97.0	48.0	Coarse and fine sand, white & yellow clay. ilminite & monozite.
4	6	9054	5	96.7	0.57	0.79	158.7	98.2	Coarse and fine sand, yellow & grey clay. granite, ilminite & pyrite.

* Grade calculated by relating recovered volume to recovered tin
Drillers reported basement at 5 m.
Total recovered volume, surface to basement 14.5 l.
Total recovered tin 1.68 g SnO2

+ Grade calculated by relating Grade from surface to inferred basement

Radford factored theoretical volume to recovered tin Rad.F = 80%
at 5 m 127.4 g SnO2 / m3 *
at 5 m 83.4 g SnO2 / m3 +

Dwg. no. : P 136 /64

115 g/m3

046122