AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.5 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 49.18 m Basement R.L.: 44.18 m Cutting Shoe / Bit diameter: 80mm Theoretical Volume: 10.1 litres

Date: 31/1/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9055	4	214.2	0.15	0.46	114.1	56.5	Fine brown silt & hard brown cement. Trace of fine tin & ilminite.
2	4	9056	6	200.2	0.09	0.24	40.8	30.3	Fine sand & grey clay. Trace of fine ilminite.
4	6	9057	5	180.9	0.47	1.22	244.9	151.5	Coarse & fine sand, grey clay small wash, granite, tin & ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 5 m. Grade from surface to inferred basement at 5 m 171.9 g SnO2 / m3 *

Total recovered volume, surface to basement 1.25 l. at 5 m 95.3 g SnO2 / m3 +

Total recovered tin 1.93 g SnO2

Dwg. no. : P 136 /64

046123