AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.K.C.6 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation.

Surface R.L.: 48.27 m Basement R.L.: 41.77 m Cutting Shoe / Bit diameter: 80mm/ 84mm Theoretical Volume: 10.1/11.1 litres

Date: 31/1/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9058	4	140.6	0.07	0.14	34.4	17.1	Yellow & grey clay, trace ilminite.
2	4	9059	7	153.8	0.05	0.11	15.5	13.4	Grey clay & yellow, fine trace of ilminite.
4	6	9060	7	112.2	0.11	0.35	49.7	39.2	Grey & yellow clay, coarse & fine sand. trace of ilminite.
6	8	9061	6	192.6	3.58	9.86	1642.9	1110.0	Yellow clay, granite, small wash. tin & ilminite.
		Bit changed from 80m -			84m				

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 6.5 m. Grade from surface to inferred basement at 6.5 m 536.2 g SnO_2/m^3 *

Total recovered volume surface to basement 19.5 l. at m 363.0 g SnO_2/m^3 +

Total recovered tin 10.46 g SnO_2

Dwg. no. : P 136 /64

046124