AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.7 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 47.89 m Basement R.L.: 41.89 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 31/1/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Sheah Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9062	6	189.9	0.12	0.33	54.6	36.9	Fine brown silt sand, Trace of fine ilminite.
2	4	9063	5	166.0	0.13	0.32	63.4	35.7	Coarse & fine sand, white & yellow clay. Trace of very fine ilminite & monozite.
4	6	9064	3	181.6	0.38	1.00	331.8	112.1	Coarse & fine sand, white & yellow clay. granite. little small wash, some tin & ilminite.
6	8	9065	2	214.1	0.13	0.40	199.7	45.0	granite, coarse & fine sand, miner wash, mono/ilmi

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 6 m. Grade from surface to inferred basement at 6 m 216.5 g SnO2 / m3 *

Total recovered volume surface to basement 14 l. at 6 m 76.6 g SnO2 / m3 +

Total recovered tin ..... g SnO2

Dwg. no. : P 136 /64

046125