AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.9 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 51.88 m Basement R.L.: 47.38 m Cutting Shoe / Bit diameter: 80.4 mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9069	6	104.3	0.22	0.33	55.4	41.2	Fine silty sand, brown cement. Trace of monozite.
2	4	9070	7	185.3	0.17	0.44	63.5	55.0	Fine silty sand, Trace of ilminite & monozite.
4	6	9071	8	121.3	0.53	0.91	113.9	112.7	Coarse and fine sand, granite, yellow clay, some small wash, Trace tin, ilminite, monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 4.5 m. Grade from surface to inferred basement at 4.5 m 103.5 g SnO_2/m^3 *

Total recovered volume, surface to basement 15 l. at 4.5 m 92.8 g SnO_2/m^3 +

Total recovered tin 1.89 g SnO_2

112.7

Dwg. no. : P 136 /64

046127