AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.10 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 50.95 m Basement R.L.: 46.15 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9072	6	119.9	0.16	0.27	45.6	33.9	Fine silty sand, yellow clay, brown cement, trace monozite, ilminite.
2	4	9073	5	87.1	0.30	0.38	75.4	46.7	C&F sand, yellow & grey clay, brown cement, trace of ilminite & monozite.
4	6	9074	6	119.1	0.35	0.59	99.1	73.6	C&F sand, decomposed granite, little bit of wash. Trace of tin & ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 4.8 m. Grade from surface to inferred basement at 4.8 m 91.7 g SnO2 / m3 *

Total recovered volume, surface to basement 13.4 l. at 4.8 m 64.2 g SnO2 / m3 +

Total recovered tin 1.25 g SnO2

93-3

Dwg. no. : P 136 /64

046128