AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.11 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 50.76 m Basement R.L.: 46.01 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9075	8	168.3	0.17	0.40	50.2	49.7	Coarse & fine sand, orange & brown clay, Trace of ilminite & monozite.
2	4	9076	9	110.9	0.11	0.15	17.2	19.2	Coarse & fine sand, yellow & grey clay. Trace of monozite, ilminite.
4	6	9077	3	198.0	0.82	2.32	773.4	287.2	Coarse & fine sand, some small wash, granite. Tin & ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 4.75 m. Grade from surface to inferred basement at 4.75 m 354.0 g SnO2 / m3 *

Total recovered volume, surface to basement 18.13 l. at 4.75 m 149.9 g SnO2 / m3 +

Total recovered tin 2.87 g SnO2

158.3

Dwg. no.: P 136 /64

046129