AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.13 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 48.79 m Basement R.L.: 44.29 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9081	6	163.3	0.11	0.25	41.4	30.8	Orange & grey clay & top soil. Trace of fine ilminite.
2	4	9082	6	184.5	0.31	0.82	136.32	101.2	Orange & grey clay, coarse & fine sand, some small wash. Tin & ilminite.
4	6	9083	8	196.6	0.57	1.61	201.9	199.9	Coarse & fine sand, yellow clay, small wash granite, Tin, ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 4.5 m. Grade from surface to inferred basement at 4.5 m 168.7 g SnO_2/m^3 *

Total recovered volume, surface to basement 14 l. at 4.5 m 147.5 g SnO_2/m^3 +

Total recovered tin 2.68 g SnO_2

191.4

Dwg. no.: P 136/64

046130