AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.14 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 48.22 m Basement R.L.: 44.72 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9084	7	110.2	0.30	0.47	66.7	57.7	Coarse & fine sand, yellow & grey clay, small wash, Ilminite & monozite.
2	4	9085	6	91.4	1.20	1.57	262.1	194.6	Coarse & fine sand, yellow & grey clay, small wash tin & ilminite.
4	6	9086	3	150.7	0.23	0.49	164.6	61.1	Granite, Trace of ilminite & monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 3.5 m. Grade from surface to inferred basement at 3.5 m 281.9 g SnO_2/m^3 *

Total recovered volume, surface to basement 11.5 l. at 3.5 m 179.1 g SnO_2/m^3 +

Total recovered tin 2.53 g SnO_2

220.0

Dwg. no.: P 136/64

046131