AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.15 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 46.38 m Basement R.L: 44.88 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9087	6	103.5	0.45	0.66	110.5	82.1	Coarse & fine sand, yellow clay, small wash, brown cement. Trace of tin & ilminite.
2	3	9088	6	129.7	0.08	0.14	23.9	17.8	Decomposed granite. Trace of ilminite & monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 1.5 m. Grade from surface to inferred basement at 1.5 m 179.3 g SnO_2/m^3 *

Total recovered volume, surface to basement 4.50 l. at 1.5 m 133.1 g SnO_2/m^3 +

Total recovered tin 0.81 g SnO_2

180.0

Dwg. no.: P 136/64

046132