AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No. M.R.C.16 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 45.03 m Basement R.L.: 42.28 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 1/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: S. Moore Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9089	7	142.4	0.15	0.31	43.62	37.8	Fine silty sand, some grey clay. Trace of monozite & ilminite.
2	4	9090	6	131.5	0.15	0.28	46.6	34.6	Decomposed granite, trace of ilminite & monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 2.75 m. Grade from surface to inferred basement at 2.75 m 65.6 g SnO_2/m^3 *

Total recovered volume, surface to basement 9.25 l. at 2.75 m 52.6 g SnO_2/m^3 +

Total recovered tin 0.58 g SnO_2

62-7

Dwg. no. : P 136/64

046133