AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.37 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L: 54.77 m Basement R.L: 51.27 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9146	6	157.5	0.57	1.28	212.9	143.8	Coarse & fine sand, brown cement, small wash Tin & ilminte.
2	4	9147	5	149.4	0.27	0.57	114.1	64.2	Coarse & fine sand, yellow & grey clay. Granite, trace tin & ilminite.
4	6	9148	6	116.0	0.15	0.24	40.3	27.2	Granite - monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 3.5 m. Grade from surface to inferred basement at 3.5 m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 9.75 l. at 3.5 m 134.5 g SnO_2/m^3 +

Total recovered tin 2.09 g SnO_2

214·4

Dwg. no.: P 136/64

046153