AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.38 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis drilling Reverse Circulation

Surface R.L.: 55.99 m Basement R.L.: 52.24 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: M. Moore Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9149	10	205.9	0.16	0.46	45.7	51.4	Coarse & fine sand, orange & grey clay, small wash. Trace v/fine tin & ilminite.
2	4	9150	7	231.2	0.31	1.02	146.2	115.3	Coarse & fine sand, white clay, trace of small wash. Tin, ilminite & monozite.
4	6	9151	5	187.0	0.13	0.34	67.8	38.2	Coarse & fine sand, granite, ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad F = 80%

Drillers reported basement at 3.75 m. Grade from surface to inferred basement at 3.75 m ..... g SnO2 / m3 *

Total recovered volume, surface to basement 16.13 l. at 3.75 m 109.3 g SnO2 / m3 +

Total recovered tin 1.82 g SnO2

112.8

Dwg. no. : P 136 /64

046154