AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.39 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 53.26 m Basement R.L.: 48.26 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade • g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9152	8	130.6	0.23	0.43	53.5	48.2	Fine & coarse sand, brown cement. v/fine trace of tin & ilminite.
2	4	9153	4	129.7	0.16	0.29	72.1	32.5	Coarse & fine sand, yellow & grey clay. Trace of ilminite & monozite.
4	6	9154	7	91.5	2.85	3.73	532.7	419.9	Coarse & fine sand, grey & yellow clay. Tin (high grade)

• Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 5 m. Grade from surface to inferred basement at 5 m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 15.5 l. at 5 m 200.2 g SnO_2/m^3 +

Total recovered tin 4.44 g SnO_2

286.5

Dwg. no. : P 136 /64

046155