AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.40 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 51.93 m Basement R.L.: 47.68 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9155	6	89.6	0.22	0.28	47.2	31.9	Fine sand, brown cement. Trace of ilminite & monozite.
2	4	9156	6	92.7	1.64	2.17	361.1	244.0	Fine sand, med.-small wash, yellow & grey clay, Coarse tin & ilminite.
4	6	9157	5	83.5	0.15	0.17	34.7	19.5	Granite, coarse & fine sand. Trace ilminite, monozite.

* Grade calculated by relating recovered volume to recovered tin. Drillers reported basement at 4.25 m. Total recovered volume, surface to basement 12.63 l. Total recovered tin 2.62 g SnO2

+ Grade calculated by relating Grade from surface to inferred basement

Radford factored theoretical volume to recovered tin Rad F = 80%: at 4.25 m ..... g SnO2 / m3 *; at 4.25 m 139.0 g SnO2 / m3 +

2074

Dwg. no.: P 136 /64

046156