AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.41 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 51.00 m Basement R.L.: 46.00 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Metres To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9158	2	242.1	0.18	0.62	307.8	69.3	Coarse & fine sand, brown cement, orange clay, small wash. V/fine trace tin & ilminite.
2	4	9159	7	127.0	0.19	0.34	48.5	38.2	Coarse & fine sand, white & grey clay small wash, Trace of tin & ilminite.
4	6	9160	5	201.4	1.45	4.18	835.1	470.2	Coarse & fine sand, granite. Tin, ilminite & monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 5 m. Grade from surface to inferred basement at 5 m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 11.5 l. at 5 m 231.1 g SnO_2/m^3 +

Total recovered tin 5.13 g SnO_2

446.1

Dwg. no.: P 136/64

046157