AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.42 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 49.99 m Basement R.L.: 45.24 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9161	7	97.5	0.14	0.19	27.0	21.3	Fine sand, grey & yellow clay. Trace ilminite.
2	4	9162	6	93.2	1.41	1.88	312.7	211.4	Fine & coarse sand, small wash, grey clay. Tin & ilminite.
4	6	9163	5	106.7	0.86	1.31	262.4	147.7	Coarse & fine sand, granite, small wash. Tin & ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 4.75 m. Grade from surface to inferred basement at 4.75 m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 14.88 l. at 4.75 m 160.1 g SnO_2/m^3 +

Total recovered tin 3.38 g SnO_2

227.2

Dwg. no.: P 136/64

046158