AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No: M.R.C.43 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 47.98 m Basement R.L.: 44.48 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3.2.80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc (g)	Conc. Assay (%Sn)	Recovered Tin (g SnO_2)	Grade * g SnO_2/m^3	Grade + g SnO_2/m^3	Description of Sample
0	2	9164	4	166.1	0.16	0.38	93.8	42.2	Coarse & fine sand, grey clay, brown cement. Trace of ilminite.
2	4	9165	6	80.7	0.59	0.69	114.3	77.2	Coarse & fine sand, grey clay, granite. Tin, trace of ilminite.
4	6	9166	6	78.5	0.29	0.32	53.5	36.2	Granite, Trace of ilminite & monozite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 3.5 m. Grade from surface to inferred basement at ..... m ..... g SnO_2/m^3 *

Total recovered volume, surface to basement 8.5 l. at 3.5 m 88.9 g SnO_2/m^3 +

Total recovered tin 1.58 g SnO_2

162-4

Dwg. no. : P 136 /64

046159