AMDEX MINING LIMITED - NORTH EAST TASMANIA DRILL LOG

Area: Monarch Hole No.: M.R.C.44 Collar Co-ordinates: ..... mN ..... mE Drilling Method: Wallis Drilling Reverse Circulation

Surface R.L.: 46.90 m Basement R.L.: 43.15 m Cutting Shoe / Bit diameter: 84mm Theoretical Volume: 11.1 litres

Date: 3/2/80 Driller: A. Cameron Assistant: T. King Sample Washer: B. Shean Geologist: T. Neale

Section From	Section To	Sample No.	Recovered Volume (l)	Weight Conc. (g)	Conc Assay (%Sn)	Recovered Tin (g SnO2)	Grade * g SnO2 /m3	Grade + g SnO2 /m3	Description of Sample
0	2	9167	4	190.8	0.17	0.46	115.9	52.2	Coarse & fine sand, grey clay, brown cement. Ilminite & monozite.
2	4	9168	6	140.9	1.30	2.62	436.5	295.0	Coarse & fine sand, drift, small wash, grey clay. Tin & ilminite.
4	6	9169	4	122.7	0.16	0.28	68.8	31.0	Coarse & fine sand, granite. Trace of monozite, Ilminite.

* Grade calculated by relating recovered volume to recovered tin + Grade calculated by relating Radford factored theoretical volume to recovered tin Rad.F = 80%

Drillers reported basement at 3.75 m. Grade from surface to inferred basement at 3.75 m ..... g SnO2 / m3 *

Total recovered volume, surface to basement 9.25 l. at 3.75 m 201.7 g SnO2 / m3 +

Total recovered tin 3.36 g SnO2

363-2

046160

Dwg. no. : P 136 /64