

Augered

Progressive Depth	Depth	Core Drawn	Core Length	Casing	Recovery %			Graphic Log	Joints No. per Foot	Fluid Return	Ground Water	Remarks
					20	40	60					
3'												BLACK CLAY
5'	5'											BROWN CLAY WITH DOLOMITE PEBBLES
7'												LIGHT GREY MUDSTONE FRAGMENTS & WHITE CRISTY SANDSTONE FRAGMENTS
9'												LIGHT GREY MUDSTONE FRAGMENTS & DEEPLY WEATHERED QUARTZ FELDSPATHIC SANDSTONE
10'11"	10'							2 1 VERTICAL 1 Dip 60°				FINE BROWN FELDSPATHIC SANDSTONE DEEPLY WEATHERED BLOCKS AND FRAGMENTED CORE SLIGHTLY JOINTED FELDSPATHIC SANDSTONE - JOINTS GRAY & RUSTED
	15'							2 VERTICAL 1 Dip 60°				24" MED. - TO COARSE GRAINED QUARTZ FELDSPATHIC SANDSTONE.
18'												6" SOFT - SINK - IRON STAINED 8" RUSKY MASSIVE SANDSTONE 26" WHITE MASSIVE FELDSPATHIC SANDSTONE - WITH GRAPHITE.
22'	20'							3 JOINTS 45° - 60°				MASSIVE GREY-WHITE FELDSPATHIC SANDSTONE - JOINTED WITH RUSTED & OPEN JOINTS.
	25'											
	30'											
	35'											
	40'											
	45'											
	50'											
	55'											
	60'											
	65'											
	70'											
	75'											
	80'											
	85'											
	90'											
	95'											
	100'											

FILL 5'0"
TRIASSIC SANDSTONE

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

AREA: SUPREME COURT BUILDING SITE.	POSITION	CO-ORDINATES:	E: 5268	N: 52516	HOLE No.
LOCATION: SALAMANCA PLACE HOBART		ON LINE:	BEARING:	AT CH.	B.H.S.
GEOLOGICAL PLAN: SURVEY PLAN.	LEVEL	AT STN.:	BEARING:	DIST:	MAP SHEET No.
DATES— (a) DRILLED: 13/10/69 (b) WATER TABLE:		SURFACE:	FORMATION:	WATER TABLE:	78 82
METHOD: AUGERED & DIAMOND DIAMETER N.M.C.	INCL.	HOLE DRILLED:	ANGLE FROM HORIZONTAL:	DIRECTION:	SHEET /
SITE REMARKS: ON ROADWAY SALAMANCA PLACE NEAR MINISTERIAL GARAGE OFFICE		VERT./HOR./INC.			9 /
					SHEETS

No Core

RI No 5873

16/10/69.