

	Progressive Depth	Depth	Core Drawn	Core Length	Casing	Recovery %				Graphic Log	Joints No. per Foot	Fluid Return	Ground Water	Remarks	
						20	40	60	80						100
AUGERED	4'													BLACK CLAY - HIGH ORGANIC %	FILL
	6'	5'												AS ABOVE	6'0"
DIAMOND	8'7"													1" DEEPLY WEATHERED SANDSTONE 2" CLOSELY BEDDED FINE SANDSTONE WITH 2" MUDSTONE BANDS 1" MASSIVE GREY MUDSTONE	TRIASSIC
	12'	10'								1 DIA 80" 2 DIASK 45"				MASSIVE FINE COMPACT MUDSTONE DOORLY JOINTED & HARD.	M/STONE & S/STONE
		15'													
		20'													
		25'													
		30'													
		35'													
		40'													
		45'													
		50'													
		55'													
		60'													
		65'													
		70'													
		75'													
		80'													
		85'													
		90'													
		95'													
		100'													

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

AREA: SUPREME COURT BUILDING SITE.	POSITION	CO-ORDINATES:	E: 5268	N: 52516	HOLE No.
LOCATION: SALAMANCA PLACE, HOBART.		ON LINE:	BEARING:	AT CH.	8.146
GEOLOGICAL PLAN: SURVEY PLAN:	LEVEL	AT STN:	BEARING:	DIST:	MAP SHEET No.
DATES—(a) DRILLED: 15/10/69 (b) WATER TABLE:		SURFACE:	FORMATION:	WATER TABLE:	82
METHOD: AUGERED & DIAMOND DIAMETER N.M.L.C	INCL.	HOLE DRILLED:	ANGLE FROM HORIZONTAL:	DIRECTION:	SHEET / OF / SHEETS
SITE REMARKS: ON SALAMANCA PLACE ROAD - OUT SIDE GOVERNMENT CARPENTERS SHOP		VERT. #			

No Core

Ref No 5874