

808008

C.R.A. EXPLORATION PTY. LIMITED
DRILL CORE LOG

SHEET No. 100

TENEMENT NAME RAZORBACK No.

PLAN - MAP REFERENCE

CO-ORDINATES 4460N 277.4E AZIMUTH 250° MAG DRILLERS PARRY COMMENCED 29-9-81 DEPTH 305m HOLE No. DD21RC4RL COLLAR 235m INCLINATION -6.7° DRILL TYPE Boxers 37 COMPLETED 23-10-81 CASING LEFT

DPO No(s)

DEPTH		Core Rec. (M)	Core Size	Graphic Log	CORE DESCRIPTION	SPECIAL FEATURES Weath, Alteration, Fracturing, Veining, Mineralization	Sample No.	From (M)	To (M)	Rec (M)	ASSAY VALUES (Analysed by							
From (M)	To (M)										Sn	W	Cu	Pb	Zn	Ag	Ni	Cr
0	3.0				TRICONE		974401	3.0	11.5		6	-	15	20	65	-	2200	275
3.0	77.4				SERPENTINITE		402	11.5	17.0		-	-	5	5	50	-	2250	365
							403	17.0	23.0		-	15	-	15	50	-	2250	340
							404	23.0	28.0		7	15	-	10	50	-	2350	385
							405	28.0	34.0		-	-	5	15	55	-	2300	405
							406	34.0	40.0		-	-	-	5	50	-	2300	335
							407	40.0	47.0		-	-	-	10	50	-	2450	405
							408	47.0	53.0		-	-	5	15	55	-	2300	345
							409	53.0	59.0		-	-	-	5	50	-	2300	365
							410	59.0	65.0		-	-	-	5	45	-	2200	325
							411	65.0	71.0		-	-	5	15	50	-	2150	325
							412	71.0	77.0		-	-	5	15	55	-	2450	350
							413	77.0	83.0		-	-	-	5	55	-	2300	320
							414	83.0	89.0		-	-	-	10	50	-	2100	275
							415	89.0	95.0		-	-	-	10	65	-	2150	285
							416	95.0	101.0		-	10	-	-	60	-	2100	360
							417	101.0	107.0		-	10	-	15	55	-	2300	285
							418	107.0	113.0		-	-	-	10	70	-	2450	260
							419	113.0	119.0		-	-	-	10	60	-	2300	435
							420	119.0	125.0		-	-	5	15	55	-	2250	310
							421	125.0	131.0		-	10	-	5	55	-	2350	350
							422	131.0	137.0		-	-	-	-	60	-	2350	250
							423	137.0	143.0		-	-	-	10	60	-	2300	305
							424	143.0	149.0		-	-	5	-	70	-	2300	345
							425	149.0	155.0		-	-	-	10	65	-	2150	305
							426	155.0	161.0		-	-	-	5	65	-	2200	290
							427	161.0	167.0		-	-	-	15	65	-	2250	270
							428	167.0	173.0		-	-	-	15	75	-	2250	385
							429	173.0	179.0		-	-	-	15	60	-	2300	340
							430	179.0	185.0		-	-	-	15	65	-	2400	320
							431	185.0	191.0		-	-	-	10	60	-	2350	346

808009

C.R.A. EXPLORATION PTY. LIMITED
DRILL CORE LOG

SHEET No.2....

TENEMENT NAME RAZORBACK No.

PLAN - MAP REFERENCE.....

CO-ORDINATES..... AZIMUTH..... DRILLERS..... COMMENCED..... DEPTH..... HOLE No. RR-91, R.C. 6.

RL COLLAR..... INCLINATION..... DRILL TYPE..... COMPLETED..... CASING LEFT..... DPO No(s).....

DEPTH		Core Rec. (M)	Core Size	Graphic Log	CORE DESCRIPTION	SPECIAL FEATURES Weath, Alteration, Fracturing, Veining, Mineralization	Sample No.	From (M)	To (M)	Rec (M)	ASSAY VALUES (Analysed by.....)							
From (M)	To (M)										Sn	W	Cu	Pb	Zn	Ag	Ni	Cr
							432	191.0	197.0		-	-	-	5	65	-	2250	305
							433	197.0	203.0		-	-	-	5	60	-	2450	285
							434	203.0	209.0		-	-	-	10	75	-	2300	425
							435	209.0	215.0		-	-	-	5	80	-	2300	335
							436	215.0	221.0		-	-	-	-	65	-	2400	330
							437	221.0	227.0		-	-	-	-	70	-	2350	190
							438	227.0	233.0		-	-	-	-	70	-	2290	230
							439	233.0	239.0		-	-	-	-	70	-	2400	265
							440	239.0	245.0		-	-	-	5	70	-	2300	370
							441	245.0	251.0		-	-	5	10	70	-	2300	280
							442	251.0	257.0		-	-	-	10	65	-	2200	255
							443	257.0	263.0		-	-	-	5	65	-	2300	215
							444	263.0	269.0		-	-	5	10	70	-	2200	250
							445	269.0	277.4		3	-	15	10	80	-	1950	260
77.4	292.6				TALC-CARBONATE, QZ. RICH	<i>Pyrrhotite-rich section</i>	446	277.4	278.4		10	-	-	60	330	-	675	465
						<i>285.0 - 286.0</i>	447	278.4	279.4		15	-	-	65	105	1.0	610	405
							448	279.4	280.4		15	-	-	40	105	-	1550	700
							449	280.4	281.4		-	-	-	50	85	-	1550	815
							450	281.4	282.4		10	-	-	20	70	-	2350	690
							451	282.4	283.4		10	-	-	30	70	-	2200	780
							452	283.4	284.4		10	-	5	35	60	-	2090	870
							453	284.4	285.0		2550	-	175	65	80	-	1400	1050
							454	285.0	286.0		3050	-	1800	290	190	3.0	1350	1550
							455	286.0	287.0		140	-	45	205	215	0.5	1200	1000
							456	287.0	288.0		55	-	30	75	135	-	1400	655
							457	288.0	289.0		6	-	5	10	50	-	1400	550
							458	289.0	290.0		5	-	-	-	20	-	1200	410
							459	290.0	291.0		3	-	5	20	30	-	1150	385
							460	291.0	292.0		20	1	5	-	25	-	1250	360
							461	292.0	292.6		20	-	5	-	15	-	1550	430
72.6	305.0				HEDGE SLATE	<i>Some bedded pyrite</i>	462	292.6	297.0		9	15	25	-	65	-	1150	370

