840 50

DEPARTMENT OF MINES — TASMANIA

DIAMOND DRILL CORE RECORD

C/M | S & A | CG | GC & M | AGM & E
RECEIVED 30 JUL 1964
ANSWERED
DEPTT. OF MINES
REF. NO.

Hole No. C8/R5

Drilled by Associated Diamond Drillers Pty. Ltd.

Core Recovery + 95%

Geological Logging by—

A. B. Clark

Area of Operation Razorback Zeehan Area

Location of Site B.M.R. Grid 1855N, 210W

Date Commenced 7/5/64

Date Completed 25/5/64

Reduced Level of Site (2948)

Bearing of Hole 282° Magentic

Dip of Hole 40°

Bore Depth 607 feet

Ref No: 3506

AMG 369200E 5363700N

6 0169

DRILL RECORD				GEOLOGICAL LOG			GEOLOGICAL SECTION		ASSAY RESULTS			
Date	From	To	Core Recov.	From	To	Description	Core	Sample	Sample No.	From	To	Sn%
7/5	0'	9'	9'	0'	324'	Serpentine	5'	5'	CR90	524'1"	529'1"	tr
8/5	9'	50'	33'	324'	549'	Grey dolimite some vein sulphide	3'11"	3'11"	CR91	529'1"	533'	tr
9/5	50'	57'	7'			at 480'1', 540'-2'	2'9"	2'9"	CR92	533'	535'9"	tr
11/5	57'	102'	45'	549'	565'	Grey crystalline dolimite	2'9"	1'9"	CR93	535'9"	538'6"	tr
12/5	102'	132'	30'	565'	568'	Grey intraformational shale	2'9"	2'9"	CR94	538'9"	541'3"	.14
13/5	132'	180'	48'			with vein sulphide mineralisation	3'	3'	CR95	565'	568'	.23
14/5	180'	234'	54'	568'	572'	intraformational grit						
15/5	234'	302'	68'	572'	607'	intraformational breccia						
18/5	302'	360'	58'									
19/5	360'	446'	86'									
20/5	446'	513'	67'									
21/5	513'	551'	38'									
22/5	551'	585'	34'									
23/5	585'	607'	22'									