

## DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7525

Locality: SOUTH MOUNT CAMERON

Drill: G33 PERCUSSION Ref NO: 1792

Bore No.: 6 Commenced: 13.5.58

Completed: 20.5.58

Location of Bore: ENDURANCE TIN MINE

Co-ordinates of Collar: General AMG Co-ords: 566200 E 5429200 N of Collar:

Bearing: Bores Not plotted Inclination: Final Depth: 163

0410

Date	Footage	Total Depth	BORE LOG					Details of Ore Intersection
			From	To	Core	Thickness	Particulars of Core	
May 13	40'	40'	0'	2'		2'	Surface Soil	
" 14	60'	100'	2'	10'		8'	Clay	
" 16	25'	125'	10'	12'		2'	Fine Sandy drift	
" 19	15'	140'	12'	15'		3'	Wash	
" 20	23'	163'	15'	30'		15'	Sediment.	
			30'	47'		17'	Fine puggy drift.	
			47'	50'		3'	Pug.	
			50'	80'		30'	Brown Puggy drift.	
			80'	96'		16'	White Puggy drift.	
			96'	125'		29'	Drift.	
			125'	158'		33'	Hard Puggy drift.	
			158'	163'		5'	Soft granite.	

**DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.**

7825

Locality: WILTSHIRE Drill: G33 PERCUSSION DRILL

Bore No: 103 Commenced: 30.5.58 Completed: 6.6.58

Location of Bore: WILTSHIRE, R.E. HANSON'S PROPERTY

Co-ordinates of Collar: ..... R.L. of Collar: 36 321

Bearing: ..... Inclination: VERTICAL Final Depth: 122 feet

Date 1958	Footage	Total Depth	BORE LOG				Particulars of Core	Details of Ore Intersection
			From	To	Core	Thickness		
MAY 30	26'	26'	0'	2'	-	2'	Surface	Struck Water at 80 feet. Flow 200 gals per hour Quality good.
JUNE 2	34'	60'	2'	26'	-	24'	Basaltic Clay	
" 3	20'	80'	26'	45'	-	19'	Clay and Stones	
" 4	15'	95'	45'	80'	-	35'	Mudstone	
" 5	15'	110'	80'	122'	-	42'	Hard Mudstone	
" 6	12'	122'						