

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: Antimonial Lead Veins, W. Bischoff, Naratah Drill: Junior Straightline - N03 D.D.  
 Bore No.: 2 Commenced: 16-9-48 Completed: 12-11-48 Ref No: 1794  
 Location of Bore: Near Compressor Shed See Plan 1033/36 and 1033B/36  
 Co-ordinates of Collar: AMG Co-ords: 375850 E 5411700 N R.L. of Collar: 30 325  
 Bearing: 80° Inclination: 36° Final Depth: 290'

0421

		BORE LOG							Details of Ore Intersection
Date 1948	Footage	Total Depth	From	To	Core	Thickness	Particulars of Core		
Sep	16	7' 0"	7' 0"	0' 0"	14' 0"	—	14' 0"	Boulders, Rubble & Sand	
	17	7' 0"	14' 0"	14' 0"	22' 7"		8' 7"	" " "	
			22' 7"	22' 7"	39' 0"	16' 0"	16' 5"	Slate	
Oct	1	17' 0"	39' 0"	39' 0"	95' 6"	50' 0"	56' 6"	"	
	6	23' 0"	62' 0"	95' 6"	95' 11"	0' 5"	5"	Mixture of Fluorite, Jamesonite, Zinc	
	7	20' 0"	82' 0"	95' 11"	96' 3"	0' 4"	4"	Mineralized Slate	
	8	18' 0"	100' 0"	96' 3"	96' 3 1/2"	0' 0 1/4"	1/4"	Fluorite	
	11	13' 0"	113' 0"	96' 3 1/2"	96' 10"	0' 6 3/4"	6 3/4"	Mineralized Slate	
	12	15' 0"	128' 0"	96' 10"	96' 10 1/2"	0' 0 1/2"	1/2"	Zinc & Fluorite	
	14	13' 0"	141' 0"	96' 10 1/2"	97' 5"	0' 6 1/2"	6 1/2"	Mineralized Slate	
20	20	5' 0"	146' 0"	97' 5"	97' 5 1/4"	0' 0 1/4"	1/4"	Fluorite	
	21	10' 0"	156' 0"	97' 5 1/4"	97' 10"	0' 4 3/4"	4 3/4"	Mineralized Slate	
	22	8' 0"	164' 0"	97' 10"	97' 10 1/2"	0' 0 1/2"	1/2"	Fluorite	
	27	10' 0"	174' 0"	97' 10 1/2"	99' 0"	1' 1 1/2"	1' 1 1/2"	Mineralized Slate	
	28	10' 0"	184' 0"	99' 0"	99' 0 1/2"	0' 0 1/8"	1/8"	Zinc	
	29	12' 0"	196' 0"	99' 0 1/2"	100' 0"	0' 11 7/8"	11 7/8"	Mineralized Slate	
Nov	3	14' 0"	210' 0"	100' 0"	101' 0"	1' 0"	1' 0"	" "	
	4	12' 0"	222' 0"	101' 0"	101' 6"	0' 6"	0' 6"	Jamesonite, Fluorite, Zinc	
	5	15' 0"	237' 0"	101' 6"	103' 0"	1' 6"	1' 6"	Mineralized Slate	
	8	10' 0"	247' 0"	103' 0"	104' 6"	1' 6"	1' 6"	Quartzite,	
	9	12' 0"	259' 0"	104' 6"	115' 0"	10' 0"	10' 6"	Slate	

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: West Bischoff, Warratah Drill: N° 3 D D  
 Bore No.: N° 2 (continued) Commenced: 16-9-48 Completed: 12-11-48  
 Location of Bore: \_\_\_\_\_  
 Co-ordinates of Collar: AM6 6° 00' S; 37° 45' 0" E SH 1170.0 N R.L. of Collar: \_\_\_\_\_  
 Bearing: 90° Inclination: 36° Final Depth: 290'

Date 1948	Footage	Total Depth	BORE LOG					Particulars of Core	Details of Ore Intersection Remarks
			From	To	Core	Thickness			
<del>Nov</del> Oct 10	11' 0"	270'	115' 0"	115' 2"	0' 2"	0' 2"	Jamesonite, Fluorite ✓		
11	10' 0"	280'	115' 2"	137' 0"	20' 2"	21' 10"	Slate		
12	10' 0"	290'	137' 0"	138' 0"	0' 1"	0' 1"	Breccia		
			138' 0"	141' 0"	3' 0"	3' 0"	Slate		
			141' 0"	151' 9"	10' 0"	10' 9"	.		
			151' 9"	153' 0"	1' 3"	1' 3"	Jamesonite Ore, good quality ✓		
			153' 0"	153' 3"	0' 3"	0' 3"	Slate		
			153' 3"	153' 4"	0' 1"	0' 1"	Jamesonite ✓		
			153' 4"	164' 0"	10' 0"	10' 8"	Slate		
			164' 0"	196' 0"	31' 6"	32' 0"	Dark Mineralised slate		
			196' 0"	237' 0"	40' 0"	41' 6"	Slate, a little mineral pyrites, some breccia		
			237'	274'	37'	37'	Slate, some lightly mineralized with a few small		
			274'	274' 2"	0' 2"	0' 2"	Zinc blende & quartz patches of breccia		
			274' 2"	290'	15' 10"	15' 10"	Slate		

0422