

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: Rossarden (H.E. Brock) Drill: Goldfields No 10 D.D.  
 Bore No.: 4 Commenced: 17-11-52 Completed: 21-11-52  
 Location of Bore: .....  
 Co-ordinates of Collar: General AMG Co-ords: 561400 E 5387150 N R.L. of Collar: .....  
 Bearing: ..... Inclination: 50° Final Depth: 53' Ref No 7457

BORE LOG

| Date   | Footage | Total Depth | From  | To    | Core | Thickness | Particulars of Core                  | Details of Ore Intersection                                                                                                                                        |
|--------|---------|-------------|-------|-------|------|-----------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1952   |         |             |       |       |      |           |                                      |                                                                                                                                                                    |
| Nov 11 | 10'     | 10'         | 0     | 6'    | -    | 6'        | Surface soil & sandstone             | Reported by H.E. Brock<br>That section 28ft to 32ft<br>analysed 1.5% Sn<br>and section 42ft to 46ft<br>analysed 3.5% Sn.<br><br>no record of Analyses in<br>office |
| 17     | 10'     | 20'         | 6'    | 10'   | 2'   | 4'        | Sandstone                            |                                                                                                                                                                    |
| 18     | 10'     | 30'         | 10'   | 11'   | 1'   | 1'        | Slate                                |                                                                                                                                                                    |
| 19     | 10'     | 40'         | 11'   | 12'6" | 1'5" | 1'6"      | <del>Quartzite &amp; Sandstone</del> |                                                                                                                                                                    |
| 20     | 8'      | 48'         | 12'6" | 13'6" | 1'   | 1'        | Slate                                |                                                                                                                                                                    |
| 21     | 5'      | 53'         | 13'6" | 23'   | 5'6" | 9'6"      | Quartzite & sandstone                |                                                                                                                                                                    |
|        |         |             | 23'   | 25'   | 1'6" | 2'        | Sandstone                            |                                                                                                                                                                    |
|        |         |             | 25'   | 29'   | 3'   | 4'        | Slate & sandstone                    |                                                                                                                                                                    |
|        |         |             | 29'   | 32'   | 1'6" | 3'        | Quartzite & sandstone                |                                                                                                                                                                    |
|        |         |             | 32'   | 53'   | 15'  | 21'       | Quartzite                            |                                                                                                                                                                    |

0500