REF No 18624 C 1854

CLEVELAND TIN — GEOLOGY DEPT.

C 1854

DRILL HOLE RECORD SHEET

Location: 7/L SURFACE ROAD

Sect: D

Objective: BATTERY

Category: P.A.

Proposed Azimuth: 290°

Proposed Dip: -23°

Survey P/U Azimuth: 291° 02'

Survey P/U Dip: -22° 55'

Instrument Azimuth Correction Factor:

Collar Co-ords: 15316.97 N. 10855.92 E.

Collar R.L.: 1342.90

Final Depth: 80.0m

Drilled By: P. PHILPOT D250

Rig Type: D250

Core Size: TT46

Drilling Commenced: 19/10/82

Drilling Completed: 27/10/82

Survey Data				Interpolated Data		
Survey Inst.	Depth	Az.	Dip	Depth	Az.	Dip
SURV. P/U.	0	291°	-23°	0	291°	-23°
CAM AMH	1.0	7HREFARO	-23.5	12.5	291°	-23.5°
" "	7.0	289	-23.0	37.5	291°	-23.5°
" "	30.0	289	-23.5	62.5	291°	-22.5°
" "	55.0	289	-23.0	80.0	290°	-22°
" "	76.0	290	-22°			

44 440

SMITH PRINT

CLEVELAND TIN - GEOLOGY DEPT.

SAMPLE ASSAY DATA

FINAL ASSAY REPORT

COST CODE: 103 c
COMPILATION DATE: 5-11-82
COMPILED BY: [illegible]
ASSAY DATES:

PAGE 1 OF 1

SAMPLE NUMBER	D.D.H. NUMBER	FACE/STOPE LENS	LEVEL	DATE	Σ	FROM	TO	LENGTH	ROCK TYPE	%SnT	%SnS	%Cu	%WO3	%MoS2	%Bi	%CaF2
401 167	C 1954					42.7	43.1	0.4	L	0.41	<0.01	0.45				
168						43.1	43.5	0.4	MIN CM	0.11	0.01	0.06				
169						43.5	44.5	1.0	L	0.80	0.06	0.23				
170						44.5	45.5	1.0	L	0.86	0.13	0.37				
401 171						45.5	46.1	0.6	L	0.98	0.08	0.35				
		BATTERY E			Σ	42.7	46.1	3.4		0.72	0.07	0.28				

1000 1/82 SMITH PRINT