

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: Seymour Drill: Sally
 Bore No.: 2 Commenced: 27th February 1945 Completed: 20th April
 Location of Bore: 10 chains west from No. 1 Rj no: 1886
 Co-ordinates of Collar: AM66ords: 606700E 5377500N R.L. of Collar: _____
 Bearing: _____ Inclination: Vertical Final Depth: 159'0"

BORE LOG

Details of Ore Intersection

Date	Footage	Total Depth	From	To	Core	Thickness	Particulars of Core
27	2	12'	0'	2'	2'	2'	Surface
28	2	9'	2'	3'	1'	1'	Sand
1	3	9'	3'	12'	9'	9'	Sandy clay
2	3	10'	4'	22'	6'	10'	Soft black mud
7	3	7'	22'	39'	8'	17'	Mudstone
9	3	11'	39'	58'	16'	19'	Mudstone
10	3	6'	58'	63'	4'	5'	Pelopathic sandstone
17	3	9'	63'	72'	9'	9'	Pelopathic sandstone
19	3	4'	72'	103'	25'	31'	Sandstone with carbonaceous seams
20	3	9'	103'	107'	3'6"	4'	" " " "
21	3	4'	107'	111'	4'	4'	" " " "
22	3	6'	111'	117'	5'	6'	Pelopathic sandstone
23	3	8'	117'	120'	3'	3'	Mudstone
25	3	4'	120'	122'	2'	2'	Pelopathic sandstone
4	4	7'	122'	125'	2'6"	3'	" "
5	4	6'	125'	130'	4'6"	5'	Shale
6	4	2'	130'	142'	11'	12'	Pelopathic sandstone
9	4	6'	142'	151'	7'4"	9'	" "
10	4	5'	151'	155'6"	1'9"	4'6"	Coal
13	4	9'	155'6"	159'0"	2'0"	3'6"	Sandstone with carbonaceous seams
16	4	4'	142'				
17	4	4'	146'				
18	4	3'	150'				
19	4	4'	153'				
		4'	157'				
		4'	159'				