

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

805

Locality: Cuni Prospect; 5 mile Zeehan Drill: Goldfields No 10
 Bore No: 1 (M6 by Montana) Commenced: 4-11-55 Completed: 8-12-55 27-1-56
 Location of Bore: 5 mile Zeehan (Cuni North see plan in draftsman office)
 Co-ordinates of Collar: AM6 60 rods: 366361 E 5367846 N R.L. of Collar: Surface
 Bearing: 312° Mag Inclination: -45° Final Depth: 161 Ref No: 1904

Date	Footage	Total Depth	BORE LOG					Particulars of Core	Details of Ore Intersection
			From	To	Core	Thickness			
Nov. 4	10'	10'	0	4'	—	4'	Only one box of core of M6 is in Hobart and this box (99-136) is the only core logged	Core held M39	
..... 8	11'	21'	4'	10'	—	6'			
..... 9	11'	32'	10	28'	—	18'			
..... 14	12'	44'	28'	29'	1	1			
..... 16	12	56'	29'	32'	2'6"	3'			
..... 21	10'	66'	32'	48'	12'	16'			
..... 22	10'	76'	48'	49'	1'	1'			
..... 23	10'	86'	49'	50'	0'6"	1'			
..... 24	10'	96'	50	52'	1'4"	2'			
..... 28	4'	100'	52	56	2'6"	4'			
Dec 8	11'	111'	56	58	1'	2'			
..... 12	7'	118'	58	60'	1'	2'			
..... 14	7'	125'	60'	72'	6'6"	12'			
..... 15	3'	128'	72'	84'	5'	12'			Pyrite at 72'
..... 19	2'	130'	84'	88	3'6"	4			
..... 21	4'	134'	88'	90	1'6"	2'			
..... 23	3'	137'	90'	96	5'6"	6'			
1956			96'	100	4'	4'			
JAN 24	1	138'	100'	111	5'	11'			
..... 25	6	144'	111'	125	13'6"	14'			
..... 26	8	152'	125	128	3'	3'			

P.T.O

34 129

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: 5 Mile Zeehan (Cul North Section) Drill: Goldfields No 10 D.D
 Bore No: 1 (ie Montana M6) Commenced: 4-11-55 Completed: 8-12-55 27-1-56
 Location of Bore: See plans in draftsman's room
 Co-ordinates of Collar: — R.L. of Collar: Surface
 Bearing: 312° Mag Inclination: -45° Final Depth: 161

BORE LOG

Date	Footage	Total Depth	From	To	Core	Thickness	Particulars of Core	Details of Ore Intersection
1956								
JAN 27	0'	161'	128'	134'	6'	6'		
			134'	136'	2'	2'		
			136'	139'	3'	3'		
			139'	161'	16'	22'		

M
 6+7
 AMG
 6-8-55

366365.51	366370.40	366293.43	366311.66	366279.88	366270.79	366284.61	366283.70	366284.61	366298.27	366275.47
5367865.26	5367837.89	5365798.21	5365802.99	5365784.34	5365779.66	5365770.68	5365770.67	5365770.68	5365775.41	

17A
 19
 19
 20
 22

0683

Locality: Five Mile Copper-Nickel Deposits Zeehan District Drill: Goldfields No 10 D.D.
 Bore No.: 1 (MG MONTANA) Commenced: 4-11-55 Completed: 8-12-55
 Location of Bore: ZEEHAN Curti North (see plans in Dept. office for location) 1266/50
 Co-ordinates of Collar: SEE ZEEHAN QUAD (BLISSETT 1962) R.L. of Collar: Surface
 Bearing: 312° Inclination: -45° Final Depth: 161'

Date		Footage	Total Depth	BORE LOG					Particulars of Core	Details of Ore Intersection
1955				From	To	Core	Thickness			
Nov	4	10'	10'	0	4'	—	4'	Surface soil		
	8	11'	21'	4'	10'	—	6'	Weathered zone.		
	9	11	32'	10'	28'		18'	" argillites		
	14	12'	44'	28'	29'	1'	1'	Slate		
	16	12'	56'	29'	32'	2'6"	3'	Argillites		
	21	10'	66'	32'	48'	12'	16'	"		
	22	10'	76'	48'	49'	1'	1'	Slate		
	23	10'	86'	49'	50'	0'6"	1'	Argillites		
Dec	24	10'	96'	50'	52'	1'4"	2'	Slate		
	28	4'	100'	52'	56'	2'6"	4'	Argillites		
	8	11	111'	56'	58'	1'	2'	"		
	12	7	118	58'	60'	1'	2'	Slate		
	14	7	125	60'	72'	6'6"	12'	Argillites	Pyrite at 72'	
	15	3	128	72'	84'	5'	12'	"		
				84'	88'	3'6"	4'	Dyke		
				88'	90'	1'6"	2'	Argillites		
			90'	96'	5'6"	6'	Dyke			
			96'	100'	4'	4'	Dyke			
			100'	111'	3'	11'	Argillites			
			111'	125'	13'6"	14'	Dyke			
			125'	128'	3'	3'	Ore body in Dyke			

34 130

DEPARTMENT OF MINES, TASMANIA—DRILLING RECORD.

7825

Locality: 5 MILE COPPER NICKEL DEPOSITS ZEEHAN DISTRICT GOLDFIELDS NO. 10. DD

Bore No.: 1. CONTINUED Commenced: Completed: 27.1.56

Location of Bore:

Co-ordinates of Collar: R.L. of Collar:

Bearing: Inclination: 45° Final Depth: 161'

Date	Footage	Total Depth	BORE LOG					Details of Ore Intersection	
			From	To	Core	Thickness	Particulars of Core	From	To
1955.									
DEC 19	2	130	128	134	6'	6'	ORE BODY IN DYKE		
21	4	134	134	137	3'	3'	DYKE		
23	3	137							
1956									
Jan 24	1	138	136'	139'	3'	3'	Lode	136'	139'
25	6	144'	139'	161'	16'	22'	Argillites		
26	8'	152'							
27	9'	161'							

0000