



# PAMINCO EXPLORATION DIAMOND DRILL CORE RECORD


341093

E No. *TF7*

Page of

LOCATION	<i>Farrell</i>	<b>OBJECTIVE</b>  <i>To test for shallow extensions to Farrell Lodes.</i>					<b>LOCATION/SURVEY DATA (AMG)</b>					
PROJECT	<i>Tullah</i>						Grid	AMG	<i>FARRELL</i>	RL Collar m <i>250.32/249.50</i>		
PROSPECT							Northing m	<i>5379070.17</i>	<i>2840.49</i>	Bearing Collar <i>111° AMG</i>		
DESIGNED BY	<i>ANL</i>						Easting m	<i>385883.30</i>	<i>3190.38</i>	Dip Collar <i>-60</i>		
LOGGED BY	<i>ANL</i>	DH Survey Type				Length Hole m <i>51.2</i>						
RELOGGED		<b>RESULT</b>  <i>Narrow lode intersection between 37.6 + 39.5m.</i>					Depth m	Bearing	Dip	Depth m	Bearing	Dip
COMMENCED	<i>March 1996</i>											
COMPLETED	<i>March 1996</i>											
DRILLED BY	<i>A/E (L. Stebbins)</i>											
DRILL RIG	<i>Gopher</i>											
<b>SIGNIFICANT INTERSECTIONS</b>												
From m	To m	Interval m	Pb	Zn	Ag.	Comments						
<i>37.6</i>	<i>39.5</i>	<i>1.9</i>	<i>11.87</i>	<i>0.24</i>	<i>320</i>	<i>True width = 1.7m.</i>						
<b>SIGNIFICANT CORE LOSS</b>			<b>POOR GROUND CONDITION ZONES</b>									
From m	To m	% Lost	From m	To m	Condition							
<b>HOLE SIZE</b>			<b>HOLE CONDITIONS AFTER COMPLETION</b>									
Size	Depth m	Collar	<i>Marked by a wooden stake</i>									
<i>52.2mm</i>	<i>0-51.2m</i>	Steel Casing										
		PVC Casing										
		Ground Water										
		Wedge										
		Drill Pad	<i>On track.</i>									



Project:		PASMINGO EXPLORATION				Hole N o.: TF7	
Logged by:		DIAMOND DRILL LOG				Page of	
Date:							
From	To	L-Cod	Lithology	Graphic(mm)	Structure	Alteration	Min
m/ft	m/ft			.06 .5 2 8 32	Angles to LCA	(wk) mod stg!	
41	51.2	Sbsh	Black shale, very deformed, zone of severe structural disruption from 41.0-51.2m. EOH 51.2m		m	cb (sil)	traces gal and sph in stringers.
					50		
					60		
					70		
					80		

*Zone of chaotic structural disruption.*

*S<sub>1</sub> ← 65*