

ORIECO PROJECT

99ORDD3

HOLE NO: 99ORDD3	SECTION:	GRID:
------------------	----------	-------

<p>PROJECT CODE</p> <p>TENEMENT : EL 1/98</p> <p>PROSPECT : ORIECO</p> <p>GRID</p> <p>MAP REFERENCE : SCAMANDER TIER</p> <p>LOCATION : SE ORIECO</p> <p>HOLE TYPE : DIAMOND</p> <p>**COLLAR COORDINATES AND RL**</p> <p>SURVEYED:</p> <p>AMG 5413360N 601250E 120RL</p> <p>PRE-COLLAR DEPTH NIL</p> <p>FINAL DEPTH 116.50</p> <p>PURPOSE OF HOLE : Exploration</p> <p>HOLE STATUS : Complete</p> <p>COMMENTS : Testing gossan outcrop</p> <p>SURVEY DATA</p> <table border="1"> <tr> <td>Survey Method:</td> <td colspan="3">Eastman Single Shot</td> </tr> <tr> <td>Depth</td> <td>Azimuth</td> <td colspan="2">Inclination</td> </tr> <tr> <td>30.5</td> <td>320</td> <td colspan="2">50</td> </tr> <tr> <td>116.5</td> <td>317</td> <td colspan="2">53</td> </tr> </table> <p>SUMMARY LOG</p> <p>0.00-99.80m Quartz Sandstone</p> <p>99.80-116.50m Interbedded Quartz Sandstone and Siltstone</p>	Survey Method:	Eastman Single Shot			Depth	Azimuth	Inclination		30.5	320	50		116.5	317	53		<p>** DRILLING SUMMARY**</p> <p>DIAMOND 116.50 BQTK</p> <p>Drilling Contractor : LIDDS</p> <p>Drill Rig: : Gopher 28</p> <p>Date Started : 28 February 1999</p> <p>Date Completed : 7 March 1999</p> <p>Logged By : AG</p> <p>Sampled By : AG</p> <p>Material Left in Hole : NIL</p> <p>Base of Complete Oxidation : 59.80m</p> <p>Top of Fresh Rock : 103.80m</p> <p>Water First Encountered : NIL</p> <p>Water Inflow Estimate : NIL</p> <p>SIGNIFICANT ASSAYS</p> <p>NIL</p>
Survey Method:	Eastman Single Shot																
Depth	Azimuth	Inclination															
30.5	320	50															
116.5	317	53															

ORIECO

DIAMOND DRILL LOG

99ORDD3

FROM (m)	TO (m)	GEOLOGICAL LOG	SAMPLE No	FROM (m)	TO (m)
0.00	99.80	<p>QUARTZ SANDSTONE</p> <p>Tan to pale gray coloured, fine to medium grained massive quartz sandstone. The sandstone is strongly oxidised down to 59.80m depth with strong to intense ferric oxides developed either pervasively through out the core or preferentially along fracture/joint planes. Oxides developed along the joint/fracure planes may be after fine grained sulphides/pyrite. From 59.80 to 103.80m the intensity of oxidation decreases. The quartz sandstone is massive in structure with no significant mineralisation</p>			
99.80	116.50	<p>INTERBEDDED QUARTZ SANDSTONE AND SILTSTONES</p> <p>Gray, fine grained interbedded quartz sandstone and siltstone exhibiting repetitive fining upward cycles. The basal sandstone units are typically gray in colour, massive, fine to medium grained and grade upwards into gray to black coloured, massive to bedded siltstones. Sedimentary structures developed include planar bedding, cross bedding and small scale slump structures.</p> <p>No significant mineralisation was observed within the drill hole.</p> <p>END OF HOLE 116.50 METRES</p>			