

40 084

Ry No 2270

DRILLING TARGET:—			To test Fooks lode 250 feet down dip from D.D.H. F.L. 1															
REMARKS:—			No ore intersected.															
SURVEY DATA			ASSAY DATA															
DEPTH feet	Bearing mag.	Inclin. degs.	SAMPLE No.	FROM		TO		RECOVERY			ASSAY RESULTS							
				ft.	ins.	ft.	ins.	ft.	ins.	%								
0	-	Vert																
250		88																
500	220	87																

GEOLOGICAL LOG

Logged by:— D.I. GROVES

FROM		TO		RECOVERY		DESCRIPTION	SECTION	
ft.	ins.	ft.	ins.	ft.	ins.		%	Core
19	4	203	11	7	6	1/2		
203	11	209	5	4	0			
209	5	213	5	4	0			
213	5	217	0	3	7			
217	0	217	5	0	4			
217	5	221	10	4	5			
221	10	223	1	1	2			
223	1	225	3	2	1			
225	3	227	2	1	2			
227	2	228	5	1	2			
228	5	232	3	3	10			
232	3	234	6	2	3			
234	6	237	4	2	9			
237	4	240	3	2	10			
240	3	243	8	3	0			

Continued over:—

DEPARTMENT OF MINES — TASMANIA  
DIAMOND DRILL CORE RECORD

HOLE No.:— F.L. 2	MAP SHEET No. 36	DISTRICT WARATAH	LOCATION OF SITE:— Fooks Lode
A distance of 505 feet (horizontal), bearing 249° mag. from Fooks Upper adit portal			Core held M 7
R.L. OF SITE:— 1891 feet	SITE SURVEY ON MAP No.:— 2455	CORE SIZE:— 0-147' NX 147-410' BX	
BEARING OF HOLE:— 1 -	AIR PHOTO No.:—	COMMENCED:— 410'-End AX 30/6/66	
INCLINATION OF HOLE:— Vertical	DRILL:— E 1000	COMPLETED:— 10-5-68	
CO-ORDS. OF SITE:— 377' 260' E 5411400N	DRILLER:— L. Freeman	FINAL DEPTH:— 858'	

Index Page:—







