40 284 Ryr 2319

DRILLING TARGET:—

REMARKS:—

SURVEY DATA			ASSAY DATA										
DEPTH feet	Bearing mag.	Inclin. degs.	SAMPLE No.	FROM ft. ins.	TO ft. ins.	RECOVERY ft.	ins.	%	ASSAY RESULTS Ash	Vol	Cal Value (BTU /lb)		
			1	45.04	45.86	0.65		80	29.5	18.0	10,660		

GEOLOGICAL LOG

Logged by:—

FROM ft. ins.	TO ft. ins.	RECOVERY ft. ins.	%	DESCRIPTION	SECTION Core	Sample
0	19.15	13.5	75	Coarse grained lithic sandstone with clay pellet conglomerate at 6.33 - 6.40 m. and 18.22 - 18.32 m.		
19.15	19.92	0.74		Grey mudstone carbonaceous at top		
19.92	21.38	1.52		Banded siltstone and sandstone		
21.32	21.82	0.37		Fine grained banded sandstone		
21.82	23.07	1.22		Fine grained lithic sandstone		
23.07	23.48	0.40		Medium-coarse grained lithic sandstone		
23.48	26.92	3.36		Calcareous at bottom		
26.92	45.04	17.60	97 %	Coarse grained lithic sandstone with clay pellet conglomerate at 35.21 - 35.57 m. 37.00 - 37.08 m. 37.96 - 38.90 m. 41.8 - 42.16 m.		
45.04	45.69	0.51		Coal		
45.69	45.74	0.04		Band		
45.74	45.86	0.10		Coal		
45.86	46.06	0.15		Carbonaceous mudstone		
46.06	47.88	1.45		Grey mudstone		
50.05	51.66	1.93		Grey lithic sandstone		

Continued over:—

DEPARTMENT OF MINES — TASMANIA

DIAMOND DRILL CORE RECORD

HOLE No.:— 6	MAP SHEET No.	DISTRICT KAOOTA	LOCATION OF SITE:—
			Core held M 98
R.L. OF SITE:—	SITE SURVEY ON MAP No.:—		CORE SIZE:— NMLC & BXM
BEARING OF HOLE:—	AIR PHOTO No.:—		COMMENCED:— 2/5/72
INCLINATION OF HOLE:— AMG Vertical	DRILL:— F 20C No. 2		COMPLETED:— 10/5/72
CO-ORDS. OF SITE:— 5125 E 52362 N	DRILLER:— G. Perry		FINAL DEPTH:— 51.66 m

86673 M8375