40 286 Rpt No 2320

DRILLING TARGET:—

REMARKS:—

SURVEY DATA			ASSAY DATA										
DEPTH feet	Bearing mag.	Inclin. degs.	SAMPLE No.	FROM ft. ins.	TO ft. ins.	RECOVERY ft. ins.	%	ASSAY RESULTS Ash	Vol	Cal Value (BTU / lb)			
			1	33.84	34.98	0.96	80	42.8	14.6	-			

GEOLOGICAL LOG

Logged by:—

FROM ft. ins.	TO ft. ins.	RECOVERY ft. ins.	%	DESCRIPTION	SECTION Core	SECTION Sample
2.82	3.02	0.19		Fine grained sandstone or siltstone		
3.02	3.22	0.19		Banded sandstone		
3.22	3.55	0.30	93	Fine grained sandstone or siltstone		
3.55	4.30	0.68		As above with bands and lenses of sandstone		
4.30	8.40	3.79		Medium grained lithic sandstone		
8.40	8.94	0.50		Black shale		
8.94	9.56	0.57		Grey mudstone		
9.56	9.66	0.10		Transition		
9.66	24.86	14.98		Medium grained lithic sandstone		
24.86	24.93	0.07		Grey mudstone		
24.93	31.26	6.26	98	Medium grained grey lithic sandstone		
31.26	31.82	0.45		As above with mudstone fragments		
31.82	33.74	1.91		Medium grained grey lithic sandstone		
33.74	33.84	0.10		Grey mudstone		
33.84	33.92	0.08		Soft coal		
33.92	34.13	0.17		Coal		
34.13	34.21	0.07	82	Sandstone		
34.21	34.98	0.63		Coal		
34.98	38.05	1.45	3.10	Grey mudstone		

Continued over:—

DEPARTMENT OF MINES — TASMANIA

DIAMOND DRILL CORE RECORD

HOLE No.:—	MAP SHEET No.	DISTRICT	LOCATION OF SITE:—
7		KAOOTA	Core held M98

R.L. OF SITE:—	SITE SURVEY ON MAP No.:—	CORE SIZE:— NMLC & BXM
BEARING OF HOLE:—	AIR PHOTO No.:—	COMMENCED:— 2/5/72
INCLINATION OF HOLE:— AMG	DRILL:— F 20C No. 2	COMPLETED:— 10/5/72
CO-ORDS. OF SITE:— 5125E 5362N.	DRILLER:— G. Perry	FINAL DEPTH:— 38.91 M

Index Page:—