

EL 6/68

40 354

TEXINS DEVELOPMENT PTY.LTD.  
SOUTH MT. CAMERON

1.

AMG 579245E 5455545N.

No Core held.

K. Harper

25/3/70

M. Kerrison

in  
casing

%

oz.

Driller's Report

Depth (ft)	Interval (ft)	Notes	%	oz.	Driller's Report	
0	1	1.53	6.9	2.1	0.20	0.17 Surface soil
1	5	) <u>7</u> ) <u>12</u>				Gravelly clay
5	10	" 5/12 55"	2.7	0.9		Tr Sticky white clay
10	15	" 1/3 64"	0.49	1.4		Tr Gravelly white clay
15	20	" 1/3 66"	0.51	1.7		Tr " " "
20	25	" 5/12 69"	0.27	1.6		Tr " " "
25	30	" 1/3 65"	0.22	2.3		Tr Decomposed Granite Bored ahead of casing
30	35	" 73"				" " " from 30' to 60'
35	40	"				" " " From 60' Bored 1' ahead
40	45	"				" " " and then drove casing.
45	50	"				"
50	55	" $\frac{1}{2}$	Tr	24.4		" $7\frac{1}{2}$ " drive shoe to 85'
55	60	" 7/12	"	24.2		" 5-5/16 " " " 85' -125'
60	65	" $\frac{2}{3}$	"	31.7		"
65	70	" 7/12	"	33.3		"

SOUTH MT. CAMERON

1

K. Harper

25/3/70

M. Kerrison

				%	Gms	
				Sn		
70	75	1.53	11/12	Tr	54.1	Decomposed Granite
75	80	"	1 1/2	Tr	85.0	
80	85	"	1 1/2	Tr.	159.5	
85	90	.77	2/3	Tr	103.9	
90	95	"	7/12	Tr	43.4	
95	100	"	2/3	Tr	39.6	
00	105	"	5/6	Tr	32.7	
05	110	"	1	Tr	12.0	
10	115	"	1	Tr	14.0	
15	120	"	5/6	0.06	5.3	
20	125	"	1-1/12	Tr	7.5	
25	127			Tr	94.0	Solid Granite